

# SCB-6915

Entry Network Appliance

## AEWIN Technologies Co., Ltd.

Desktop Network Appliance with Intel Celeron/Pentium/Atom (Alder Lake-N), up to 6x RJ45 ports (optional 1x 2.5GbE port or 1x 1GbE SFP port), 1x DDR4 SO-DIMM, 1x SATA, 1x mSATA, 1x eMMC, 2x USB 3.0, 1x M.2



### Features

- Support Single Intel Celeron/Pentium/Atom Processor (Alder Lake-N), FCBGA1264
- 1x DDR4 SO-DIMM memory, up to 3200 MHz
- 6 x 1GbE RJ45 ports (1x optional 2.5GbE port and 1x 1GbE SFP port)
- 1x M.2 B-Key or M-Key or E-Key
- 1x 2.5" SATA, 1x mSATA, 1x eMMC 5.1

### Description

SCB-6915, powered by Intel Atom x7000E Processor (Alder Lake N) featuring upgraded computing performance with low power consumption. SCB-6915 supports DDR4 memory with up to 32GB, 3200MHz and is designed with ultra-compact size & improved energy efficiency for entry-level networking solutions.

SCB-6915 has up to 5x 1GbE ports with 1 pair of Gen3 Bypass, 1x SFP, 1x M.2 slot for multiple options including 4G/5G module, Wi-Fi module, or NVMe storage device. It is flexible for various kinds of connectivity or functions per customer request. In addition, SCB-6915 offers 2x USB 3.0, and multiple storage options (1x eMMC, 1x SATA3 2.5" SATA SSD/HDD, and 1x mSATA).

Regarding security support, it has Intel AES-NI for crypto acceleration and TPM for protected data/keys/identity. It is also with many hardware-based secure technologies for system reliability including Intel TEE (Trusted Execution Environment) for sensitive data protection, and Intel OS Guard plus Intel Boot Guard for platform integrity.

SCB-6915 is not only suitable for edge deployment, but also ideal for silence environments uses with its optional fanless design. Featuring rich I/O and reliable hardware security in a small box. SCB-6915 is perfect for diverse applications such as uCPE, firewall, cybersecurity, and more.

### Specifications

#### ▼ Processor System

CPU	Intel® Celeron® Pentium® Atom® (Alder Lake-N) SCB-6915A, B: N97 (SKU2): 4C, 12W SCB-6915C: x7211E (SKU5): 2C, 6W
-----	--

Chipset	SOC Integrated
---------	----------------

BIOS	AMI UEFI BIOS
------	---------------

#### ▼ Memory

Technology	DDR4 up to 3200MHz
------------	--------------------

Capacity	Max. 16 GB
----------	------------

#### ▼ Expansion

M.2	1x M.2 (B-Key or M-Key or E-Key)
-----	----------------------------------

#### ▼ I/O

USB	2x USB 3.0
-----	------------

Console	1x RJ45 console port
---------	----------------------

SIM	2 (SCB-6915A only)
-----	--------------------

#### ▼ Ethernet

Controller	Up to 6x Intel I210-AT Optional 1x I226-LM Optional 1x I210-IS
------------	--

GbE Ethernet	Up to 6x RJ45 Optional 1x 2.5GbE Optional 1x SFP
--------------	--

#### ▼ Storage

SATA	1x 2.5"
mSATA	1x mSATA
eMMC	up to 128GB eMMC 5.1

#### ▼ Power Supply

Watt	60W power adapter
------	-------------------

#### ▼ Mechanical and Environment

Form Factor	Desktop, Fanless
LED	Power/HDD/Status/Bypass

Dimension (W x D x H)	232mm(W) x 152mm(D) x 44mm(H)
-----------------------	-------------------------------

Operating Temperature	Operating: 0 ~ 40°C ( 32 ~ 104°F )
-----------------------	------------------------------------

Storage Temperature	-20 ~ 75°C (-4 ~ 167°F)
---------------------	-------------------------

Humidity	10 ~ 85% relative humidity, non-operating, non-condensing
----------	---

Weight	2 kg
--------	------

Certification	CE/FCC
---------------	--------

#### ▼ Packing List

- 1x SCB-6915 unit
- 1x power cord

Ordering Information

- SCB-6915A

Desktop Network System with Intel Alder Lake-N N97 Processor, 1 x DDR4 SO-DIMM, 5 x Copper GbE (Intel I210-AT), 1 x fiber GbE (Intel I210-IS), 2 x USB 3.0, 1 x SATA, 1 x mSATA, 1 x M.2 B-key connector, eMMC 8G, 1 x Bypass
- SCB-6915C

Desktop Network System with Intel Alder Lake-N x7211E Processor, 1 x DDR4 SO-DIMM, 4 x Copper GbE (Intel 3x I210-AT + 1x I226-LM), 2 x USB 3.0, 1 x SATA, 1 x mSATA, 1 x M.2 E-key connector, eMMC 8G, w/o Bypass, Fanless
- SCB-6915B

Desktop Network System with Intel Alder Lake-N N97 Processor, 1 x DDR4 SO-DIMM, 4 x Copper GbE (Intel I210-AT), 2 x USB 3.0, 1 x M.2 M-key connector, eMMC 8G, w/o Bypass, Fanless

I/O



LED definition:		
1~12 CB-6915A	6 pairs LEDs for 6 Ethernet ports Active/Link status (Green)	
5~12 CB-6915B, C	4 pairs LEDs for 4 Ethernet ports Active/Link status (Green)	
13 Status	Yellow/Green (depends on sample code)	
14 HDD	Yellow	
15 Power	Green	
16 Bypass	Yellow	